

Product Specification

Product Class: LED LENS

Item No: DK-5050-132X89-TP-III-S-6H1-LUMILEDS5050

Material: PC(UV)

Certification: RoHS

Sut Up:PeiShan Wu

Check:XuanYang


Content

Specification-----	3
2D Drawing-----	4
Optical Datasheet-----	5
Packing-----	6
Application Notes-----	7

Specification

Item No	Picture	Size	Matched LED	Lighting Application
DK-5050-132X89-TP-III-S-6H1-LUMILEDS5050		diamete: 49.5*49.5MM height: 6.95MM FWHM:132*89°	5050	Street Lamp


Drawing



Optical Test Report

Packing

Material	Size	Total
Antistatic blister box	4W	20PCS a layer or deck
Box	335*245*105/mm	280PCS/ Box
Outer Box	510*330*255/mm	1120pcs/ Outer Box



Application Notes

(1) Please use a little water and soft fabric (air-laid paper) to clean the lens & reflector if necessary.

(2) Forbid to use industrial solvent to clean the lens, such as alcohol.

(3) The working temperature is $-40^{\circ}\text{C} \sim +80^{\circ}\text{C}$.

(4) Storage environment temperature is $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$, humidity is 30%~95%。

Optic Lens has the function to change the ray of light, it is made of optical material, the effect shall be influenced once pollute. Please do not open the packing before use it, to avoid the dust pollution.

(5) Protect the product from the sun and other ultraviolet ray, as these will lead to aging, change color, crack, etc.

(6) Please wear gloves once install the lens, avoid to abrasion the lens surface.

(7) Forbid to use acidic or alkaline solution touch the product, avoid to generate the chemical reactions.