

Product Specification

Product Class: LED LENS

Item No: **DK-520-60-LENS-96H1**

Material: PC(UV)

Certification: RoHS


Content

Specification-----	3
2D Drawing-----	4
Optical Datasheet-----	5
Packing-----	6
Application Notes-----	7

Specification

Item No	Picture	Size	Matched LED	Lighting Application
DK-520-60-LENS-96H1		Diameter: 520*116mm Height:13.7mm FWHM:60°	5050	Streetlight

Drawing



Optical Test Report

产品特征

灯具制造厂商:

光源个数: 1

发光面长度(mm): 0 mm

发光面高度(mm): 0 mm

光源光通量: 1.0 lm

发光面宽度(mm): 0 mm

功率: 1.00 W

光度结果

灯具CIE分类: 直接型

灯具光通量: 1 lm

下射光通量比: 100.23%

水平扩散角(10%, 50%, 75%, 100%): H69.2, H50.8, H40.7, H10

垂直扩散角(10%, 50%, 75%, 100%): V70, V52.1, V42.1, V15

灯具光效等级(LER): 1.05

峰值光强: 1.48 cd

S/MH(C0/C180): 0.85

额定光通量: 1.0 lm

灯具效率: 100.23%


上射光通量比: 0.00%

中心光强: 1.36 cd


峰值光强位置: H175 V10

S/MH(C90/C270): 0.87



灯具实物照片



配光曲线



配光曲线



Packing

Material	Size	Packing Instruction
Pearl wool	315*230mm	44PCS/1 Carton
White Paperboard	570*250mm	
Carton	A=B 590*275*290mm	

Application Notes

- (1) Please use a little water and soft fabric (air-laid paper) to clean the product if necessary.
- (2) Forbid to use industrial solvent to clean the product, such as alcohol.
- (3) The working temperature is $-35^{\circ}\text{C}\sim+120^{\circ}\text{C}$.
- (4) Storage environment temperature is $0^{\circ}\text{C}\sim40^{\circ}\text{C}$, humidity is 30%~95%.
- (5) The product has the function to change the ray of light, it is made of optical material, the effect shall be influenced once pollute. Please do not open the packing before use it, to avoid the dust pollution.
- (6) Protect the product from the sun and other ultraviolet ray, as these will lead to aging, change color, crack, etc.
- (7) Please wear gloves once install the product, avoid to abrasion the product surface.
- (8) Forbid to use acidic or alkaline solution touch the product, avoid to generate the chemical reactions.