

Product Specification

Product Class: LED LENS Item No:DK252x70-49x21-84H1-TPIV-S Material: PC Certification: RoHS

> Set up: Xuan Yang Check: Xiaohui Liang

DARKOO 达尔科中山市达尔科光学有限公司 <u>—为控光</u>而生 Darkoo Optics (Zhongshan) Co., Ltd

Content

Specification	3
2D Drawing	4
Optical Datasheet	5
Packing	6
Application Notes	7



<u>一为控光而生</u> Darkoo Optics (Zhongshan) Co., Ltd

Specification

Item No	Picture	Size	Matched LED	Lighting Application
DK252x70-49x21-84H1-TPIV-S		Diameter: Φ70x252mm ² Height:7.64mm FWHM:49*21°	3030	Streetlight

Drawing







<u>一为控光而生</u> Darkoo Optics (Zhongshan) Co., Ltd

Optical Test Report

产品特征

灯具种类: 电压: 0.0 V 功率: 0.00 W

电流: 0.000 A 功率因数: 0.000

光度结果

 灯具CIE分类:直接型
 额定光通量:1592.1 lm

 灯具光通量:1592.1 lm
 灯具效率:100%

 下射光通量比:100%
 上射光通量比:0%

 水平扩散角(25%,50%,75%,100%):H117,H108.2,H97.4,H69

 垂直扩散角(25%,50%,75%,100%):V129,V113.3,V81.4,V60

 灯具光效等级(LER):1592
 中心光强:285.5 cd

 峰值光强:1506.94 cd
 峰值光强位置:H90 V60

灯具实物照片

配光曲线



DARKOO 达尔利中山市达尔科光学有限公司

<u>一为控光而生</u> Darkoo Optics (Zhongshan) Co., Ltd

Packing

Material	Size	Packing Instruction
White paper	White paper	
EPE	EPE(315*240)mm	xxPCS/1 Box
White Paperboard	A级(400g)310*230/mm	4 Box/1 Carton
Box	320*245*115/mm	
Carton	A=B 505*330*255/mm	



Application Notes

(1) Please use a litter water and soft fabric (air-laid paper) to clean the product if necessary.

(2) Forbid to use industrial solvent to clean the product, such as alcohol.

(3) The working temperature is $-40^{\circ}C \sim +80^{\circ}C(PMMA)$ or $-35^{\circ}C \sim +120^{\circ}C(PC)$.

(4) Storage environment temperature is $0^{\circ}C \sim 40^{\circ}C$, humidity is $30\% \sim 95\%$.

(5) The product has the function to change the ray of light, it is made of optical material, the effect shall be influenced once pollute. Please do not open the packing before use it, to avoid the dust pollution.

(6) Protect the product from the sun and other ultraviolet ray, as these will lead to aging, change color, crack, etc.

(7) Please ware gloves once install the product, avoid to abrasion the product surface.

(8) Forbid to use acidic or alkaline solution touch the product, avoid to generate the chemical reactions.